

# Straight cables

Contact us to have your own custom made cables



Part No.	No of cores	Cable outer diameter	Colour	Screening and twisting	Tie cords	Outer Material	Conductor Material	Conductor AWG	No of Braids/ Braided AWG
<b>G-9500254</b>	1	2.60	Metallic	Double braided, waxed and shielded	0	Shield	Tinned copper	22	7/30
<b>G-9500427 M (FLESH)</b>	1	1.30	Flesh	Overall screening	0	polyurethane	Bare copper	26	65/44
<b>G-9500708</b>	1	3.80	Black	-	0	PVC	Tinned copper	18	16/30
<b>G-9501375</b>	1	2.60	Black	Overall screening	0	PVC	Tinned copper	26	65/44
<b>G-9501387</b>	1	1.70	Black	Overall screening	0	polyurethane	Hard tinned cadmium copper alloy	30	19/42
<b>G-9500085 ROHS</b>	2	3.80	Black	-	0	polyurethane	Specialised hard tinned cadmium copper alloy	25	37/40
<b>G-9500267 M</b>	2	2.16	Black	Overall screening	0	polyurethane	Hard tinned cadmium copper alloy	31	7/39
<b>G-9500504 M</b>	2	4.00	Black	Overall screening	2	Polyurethane	Hard tinned cadmium copper alloy	25	37/40
<b>G-9500546 M</b>	2	1.90	Black	Overall screening	0	polyurethane	Hard tinned cadmium copper alloy	31	7/39
<b>G-9500924</b>	2	4.20	Black	-	1	polyurethane	Tinned copper	20	19/32
<b>G-9500924 M</b>	2	4.20	Black	-	1	polyurethane	Tinned copper	20	19/32
<b>G-9501008</b>	2	4.06	Black	-	2 (stay cords)	polyurethane	Hard tinned cadmium copper alloy	24	46/40
<b>G-9500086 ROHS</b>	3	4.60	Black	1 core screened	0	polyurethane	High strength alloy	25	37/40
<b>G-9500176 (BLACK)</b>	3	2.70	Black	1 core screened and insulated	2	polyurethane	Tinned copper	30	7/38
<b>G-9500731 METERS</b>	3	1.78	Black	Overall screening	0	polyurethane	Tinned copper	32	7/40
<b>G-9500087 ROHS</b>	4	4.70	Black	1 core screened	0	polyurethane	HT cad-free alloy	25	37/40
<b>G-9500730 CMS</b>	4	4.10	Black	2 pairs twisted and shielded wrapped with tie cord with overall shielding	1	polyurethane	Tinned copper	28	19/40
<b>G-9500793 M</b>	4	4.20	Black	-	1	polyurethane	Tinned copper	26	19/38
<b>G-7950070-1 M</b>	5	4.10	Black	1 core screened	1	polyurethane	Hard tinned copper alloy	28	19/40
<b>G-9500265 M</b>	6	4.70	Black	1 core screened	0	polyurethane	Hard tinned cadmium copper alloy	25	37/40
<b>G-9500579 METER</b>	6	7.60	Black	3 pairs twisted and shielded in isolation	3	polyurethane	Silver plated alloy	26	19/38
<b>G-9500978</b>	6	5.30	Black	3 pairs twisted and shielded in isolation	0	polyurethane	Specialised hard tinned cadmium copper alloy	26	19/38
<b>G-9501068</b>	6	6.00	Black	1 core screened and insulated with overall screen	0	polyurethane	Tinned copper	26	26/40
<b>G-9501384</b>	6	6.15	Black	1 core screened and insulated with overall screen	2	polyurethane	Specialised hard tinned cadmium copper alloy	26	19/38
<b>G-9501509</b>	6	3.60	Black	Overall screening	1	polyurethane	HT cad-free alloy	30	19/42
<b>G-9501228</b>	7	3.80	Black	Overall screening	1	polyurethane	Tinned copper	30	7/38
<b>G-9501276</b>	7	6.35	Black	2 pairs twisted and shielded with overall shielding	0	polyurethane	Tinned copper	26	19/38
<b>G-9501225</b>	8	4.70	Black	1 pair twisted and screened with overall screen	0	polyurethane	Tinned hard cad free alloy	26/28	(19/38)(19/40)
<b>G-9501437</b>	8	5.60	Black	2 pairs twisted and shielded with overall shielding	2	polyurethane	Specialised hard tinned cadmium copper alloy	24/28	(46/40)(40/44)
<b>G-9501397</b>	9	5.30	Black	2 cores individually screened with overall screen	1	polyurethane	Specialised hard tinned cadmium copper alloy	26	19/38
<b>G-9501013</b>	10	6.70	Black	1 core screened and insulated with overall screen	0	polyurethane	Tinned copper	24	19/36
<b>G-9501019</b>	10	6.20	Black	Each core screened separately	1	polyurethane	Bare copper	27	50/44
<b>G-9500827</b>	12	5.40	Black	Twisted into 6 pairs with overall screening	0	polyurethane	Tinned copper	26	19/38

# Coiled cables

Contact us to have your own custom made cables



Part No.	No of cores	Cable outer diameter	Approximate extended length	Retracted Length	Colour	TAIL A	TAIL B	Coil outer diameter	Screening and twisting	Tie cords	Outer Material	Conductor Material	Conductor AWG	No of Braids/ Braided AWG
<b>PED1793</b>	6			325mm		425	220		1 core screened + overall screen					26
<b>G-7980472</b>	2	3.90	2.20m	300mm	Black	85	100	14	1 twisted pair unscreened	0	polyurethane	Tinned copper	24	19/36
<b>G-7980121</b>	5	4.10	9.60m	1.1m	Black	150	150	15	1 core screened	1	polyurethane	Tinned copper	28	19/40
<b>G-7980166</b>	5	4.10	1.75m	165mm	Black	175	175	15	1 core screened	1	polyurethane	Tinned copper	28	19/41
<b>G-7980254</b>	5	4.10	2.30m	200mm	Black	170	210	15	1 core screened	1	polyurethane	Hard tinned cadmium copper alloy	28	19/40
<b>G-7980353</b>	5	4.10	8.20m	850mm	Black	320	320	15	1 core screened	1	polyurethane	28	28	19/40
<b>PAMSPC101</b>	5	4.10	3.20m	380mm	Black	175	175	16	1 core screened	1	polyurethane	Hard tinned copper alloy	28	19/40
<b>G-7980060</b>	6	6.80	2.60m	254mm	Black	320	533	25	3 twisted pairs with isolated screens	3	polyurethane	Silver plated alloy	26	19/38
<b>G-7980140</b>	6	4.30	4.50m	460mm	Black	180	180	16	2 cores individually screened	1	polyurethane	Hard tinned cadmium copper alloy	28	19/40
<b>G-7980360-RED</b>	6	6.80	7.75m	1000mm	Red	250	250	25	3 twisted pairs, one pair screened	1	polyurethane	Silver plated alloy	26	19/38
<b>G-7980360-YELLOW</b>	6	6.80	7.75m	500mm	Yellow	250	250	25	3 twisted pairs, one pair screened	1	polyurethane	Silver plated alloy	26	19/38
<b>G-7980480</b>	6	6.15	6.00m	1000mm	Black	200	200	22	1 core screened and insulated with overall screen	2	polyurethane	Hard tinned copper alloy	26	19/38
<b>G-7980484</b>	6	3.60	2.00m	164mm	Black	65	426	13.7	Overall screening	1	polyurethane	HT-CFCA	28	19/40
<b>G-7980501</b>	6	6.15	2.75m	280mm	Black	430	230	22	1 core screened and insulated with overall screen	2	polyurethane	Hard tinned copper alloy	26	19/38
<b>G-7980219</b>	7	6.40	1.30m	125mm	Black	150	150	24	2 pairs of cores twisted and screened. 3 separately twisted	0	polyurethane	Tinned copper	26	19/38
<b>G-7980483</b>	9	5.30	5.00m	460mm	Black	250	700	21.4	2 singles shielded separately	1	polyurethane	Hard tinned copper alloy	26	19/38
<b>G-7980333</b>	10	4.20	2.60m	340mm	Black	160	160	18	1 twisted pair screened	1	polyurethane	Tinned copper	30	7/38

